

Key Features

- Output Power 500mW
- Linewidth <1MHz
- Stable Single Frequency
- Low intensity noise
- Single Mode, $M^2 \approx 1$
- Standard or All-PM version
- Compact & Rugged Module
- PM Output with High PER
- USB
- Operation Temp: 10 to 45°C

Applications

- LIDAR
- Fiber Optic Sensing
- Laser Spectroscopy
- Coherent communications
- Analog & RF Photonics

MAKO SERIES

Also available at different standard wavelengths with same high performance and compact footprint:

- ◆ MAKO-NL-1064
- ◆ MAKO-NL-1550
- ◆ MAKO-NL-1900
- ◆ MAKO-NL-2000

The CYBEL MAKO-NL-BT 1030 is a single frequency narrow linewidth fiber laser designed for low noise applications. The MAKO-NL-BT 1030 benchtop unit produces a highly stable 1030nm CW output up to 500mW with a sub-MHz linewidth range, low RIN and intensity noise and excellent OSNR.

The MAKO-NL-BT 1030 design laser comes in a 19" rack mount benchtop unit with either a standard or an all polarization maintaining (PM) fiber that provides steady performance in adverse environmental conditions. External monitoring and control can be achieved via USB computer interface.



Turn-Key Rack Mount Benchtop

MAKO-NL-BT1030 Specifications

OPTICAL	Unit	Value	Comment
Center wavelength	nm	1030	Other wavelengths available
Output power	mW	500	
Output signal linewidth (3 dB)	MHz	<1	Option of 100kHz or less
Beam quality (M ²)	kHz	<1.1	
Side mode sup. ratio (SMSR)	dB	50	@Pout=1W, Res; 0.05nm
Polarization ext. ratio	dB	≥ 18	PM version
Relative intensity noise (RIN)	dBc/Hz	<120 @ 500Hz	
Output fiber stability	%	<1	With 30dB output isolator
Pigtail output fiber	m	SMF 28 or PM Panda fiber	Armored cable, optional
Fiber length	m	1	FC/APC connector termination
Output power tuning range	%	10 to 100	
ELECTRICAL/MECHANICAL			
Voltage	V	110-220	
Warm-up Time	min	20	
Mechanical package	inch	19	2U-Rack mounted benchtop
Supply power consumption	W	12	@Pout max=250mW
Control interface		USB	
ENVIRONMENTAL			
Operating temperature	°C	10 to 45	
Operating relative humidity	%	0 to 95	Non-condensing

CUSTOMIZATION

The **MAKO** is a laser platform that can be customized to match Customers' specific requirements. Please contact Cybel.

COMPLIANCE with Regulatory Requirements: These benchtop products are Class 4 lasers as designated by the Center for Device and Radiology Health (CDRH). As such they are intended only in integration into other equipment and do not comply with CDRH requirement. It is the customer responsibility for CDRH certification of the full system that incorporates this industrial laser.



1195 Pennsylvania Ave
Bethlehem, PA 18018
Phone: 610-691-7012

Sales: contact@cybel-llc.com

Website: www.cybel-llc.com